

LINE INTERACTIVE UPS



Pure Line – LI Series UPS, is designed to provide a stable output power using the built in Buck and Boost Automatic voltage Regulator for regulation.

Units are Lightweight and compact in size. Ideal for the following applications: - Computers, entry level printers, PABX systems, Point of sale, CCTV, Fax, Modem's, etc.

Models	PL-Li 650Va	PL-Li 1000Va	PL-Li 1500Va	PL-Li 3000Va
Capacity	650Va / 360W	1000Va / 600W	1500Va / 1200W	3000Va / 1800W

Input

Voltage	220/230/240VAC
Voltage Range	135V- 275 VAC
Frequency	50Hz

Output

Voltage	220/230/240VAC
Voltage Range (Battery Mode)	+/- 10%
Frequency (Battery Mode)	50HZ +/- 10%
Transfer Time	Typically 4 to 6ms
Wave form (Battery Mode)	Simulated Sinewave

Battery

Battery Model & Qty	12V7A/H x 1	12V7A/Hx2	12V9A/Hx 2	12V9A/Hx4
---------------------	-------------	-----------	------------	-----------

Charge Time 8 hours recover to 80-90% capacity

Other Features

Full Protection	Automatic detection, discharge, short circuit and overload protection
Indicators - LED	Backup, Normal Charge indication
Alarm	Battery Mode - Beeping every 4 seconds Low Battery - Beeping every second Overload - Beeping every second Fault - Continuously Sounding
Noise Level	Less than 40dB

**Standby
Systems** 